



LEGACY 1110 SEAL IT

Interior • High Hold - Out Drywall Sealer



Product Data Sheet

Edition January 8, 2015



LEGACY®

Product Description

Legacy 1110 Seal It a premium plus pigmented high-solids PVA sealer for new drywall and plaster. This product has very good enamel hold-out and sealing properties.

Certification

SCAQMD - complies with Rule 1113, Architectural Coating
LEED - complies with GS-11 / EQ 4.2.
MPI - #50

Recommended Uses

New interior drywall and plaster.

Bases

White

Packaging

One and five gallon containers

Finish

Mat @ 85° = 2.5 - 3.5 %

Surface Preparation

WARNING! Removal of old paint by sanding, scraping or other means may generate dust or fumes that contain lead. Exposure to lead dust or fumes may cause brain damage or other adverse health effects, especially in children or pregnant women. Controlling exposure to lead or other hazardous substances requires the use of proper protective equipment, such as a properly fitted respirator (NIOSH approved) and proper containment and cleanup. For more information, call the National Lead Information Center at 1-800-424-LEAD (in US) or contact your local health authority. To ensure proper adhesion, the surface to be painted must be free of dirt, dust, oil, grease, wax, rust, and any other surface contaminants. Clean surface using an appropriate cleaner. Rinse thoroughly and allow to dry. Sand or scrape surface to remove any loose paint and to smooth old surfaces. Dull glossy surfaces by using 150 grit sandpaper. Fill cracks and holes with spackling paste to smooth uneven areas. When dry, sand and remove sanding dust.

Drywall: Wipe with a damp cloth to remove dust. Allow to dry. Fill cracks & holes with spackling compound and sand smooth. Joint compound must be cured and sanded smooth. Remove all sanding dust.

Plaster: All new surfaces must be hard and cured according to the supplier's recommendations—usually at least 30 days. Treat textured, soft, porous, or powdery plaster with a solution of 1 pint household vinegar to 1 gallon of water. Repeat until the surface is hard, rinse with water and allow to dry.

Application

Temperature (air, surface, and material) 12.8°C (55°F) and relative humidity below 80%.

Airless Spray:

Pressure - 2000 psi, Tip - .015"-.021", Reduction - Not necessary.

Brush:

Brush - Nylon / Polyester, Reduction - Not recommended.

Roller:

Cover - 6 mm - 19 mm (1/4" - 3/4") synthetic, Reduction - Not recommended.

Drying Time

Touch: 1 hour • Recoat: 4 hours

Coverage

300-375 square feet per gallon, depending on surface

Mil Thickness

Wet - 4.1 • Dry - 1.5

Thinning

Use at package consistency. If thinning is required, use water sparingly.

Flash Point

N/A

DISCLAIMER: To the best of our knowledge, the technical data contained herein are true and accurate at the date of issuance and offered in good faith. All technical information is subject to change without prior notice. This product is guaranteed to give satisfactory performance if applied and used in accordance with the label instructions. Any liability shall be limited to a refund of the purchase price, or replacement of this product. This warranty does not include labor or cost of labor for the application of any coating. All express and all implied warranties are hereby disclaimed and excluded including all implied warranties of fitness for a particular use and merchantability. Final determination of the suitability of product or intended use is the sole responsibility of the user. Additional information may be obtained from your local sales representative.



LEGACY®

LEGACY 1110 SEAL IT

Interior • High Hold - Out Drywall Sealer

Product Data Sheet

Edition January 8, 2015



Clean Up

Clean spills and spatters immediately with soap and warm water. Clean hands and tools immediately after use with soap and warm water. After cleaning, flush spray equipment with mineral spirits to prevent rusting of the equipment. Follow manufacturer's safety recommendations when using mineral spirits.

Cautions

- Protect from freezing
- Non-photochemically reactive
- Not for use on horizontal surfaces or where water will collect

Composition

Titanium Dioxide 14.4%, Extenders 13.9%
TOTAL PIGMENT 28.3%
Vinyl Acrylic 20.0%, Additives 5.8%, Water 45.9%
TOTAL VEHICLE 71.7%

Weights & Measurements +/-3.0%,
Solids by Volume: 36.6%,
Solids by Weight: 50.6%
VOC: 97 g/l
Weight Per Gal: 10.73 lbs.
Viscosity: 92 KU

DISCLAIMER: To the best of our knowledge, the technical data contained herein are true and accurate at the date of issuance and offered in good faith. All technical information is subject to change without prior notice. This product is guaranteed to give satisfactory performance if applied and used in accordance with the label instructions. Any liability shall be limited to a refund of the purchase price, or replacement of this product. This warranty does not include labor or cost of labor for the application of any coating. All express and all implied warranties are hereby disclaimed and excluded including all implied warranties of fitness for a particular use and merchantability. Final determination of the suitability of product or intended use is the sole responsibility of the user. Additional information may be obtained from your local sales representative.